

## TUBE FUNCTION AND LOCATION CHART PITTBULL HUNDRED/CLX

Each 12AX7 has two sections/functions. Section A is shown first, Section B is second. Factory recommended tubes are listed under each location. Numbering sequence is right to left looking at back of amp starting with the row closest to front panel of amp.

V1 (shielded tube) 12AX7WB Sovtek	Input Gain Stage 1 and signal splitter for all 3 channels
V2 12AX7 China	Gain Stage 2 for Lead channel. Gain Stage 3 for Lead and Rhythm channels. Active when either Gain Switch is set to HI.
V3 12AX7 China	Gain Stage 4 for Lead and Rhythm channels. Tone Control Driver for Lead and Rhythm channels.
V4 12AX7 China	Gain Stage 2 for Clean channel. Gain Stage 2 for Rhythm channel.
V5 12AX7 China	Phase Inverter
V6-9 EL34 Svetlana	Power Tubes.

### NOTE:

EARLIER MODELS EQUIPPED WITH REVERB ARE FITTED WITH AN EL84 REVERB DRIVER TUBE. AN EF86 REVERB DRIVER IS USED ON MORE RECENT MODELS. NEITHER OF THESE TUBES ARE INTERCHANGABLE WITH PREAMP TUBES SUCH AS 12AX7, 12AU7, 12AT7 OR THEIR VARIANTS.